Order Name / No.:	Order Date	:
Company Name:	Quantity:	
DIMENSIONS W - Total Widthcm P - Projectioncm C - Wall / Back Heightcm H - Front / Post Heightcm Total Number of Posts Requiredpc (Maximum span between posts with gutter profile is 600cm)		 If modules are multiple and each module is in different width, please provide details (max. width for single module is 450cm, double modules 900cm, triple modules 1300cm) W 1cm W 2cm W 3cm
POWDERCOJORSRAL colorsExclusive colorsTexture colorsRAL 9016OGN35ST9010RAL 1013OS561ST9001RAL 9006OY395ST1013RAL 7006OGN39ST7039RAL 7016ON617ST7016RAL 9005ON611ST8019	Other	FABRICBasicTransparentWT785 / WhiteTRW22 / WhiteOtherCR295 / CreamTRB33 / BlackXclusiveMattWTEX / WhiteMW23 / WhiteCRMX / CreamMC26 / CappuccinoGRYX / GreyMatt
OPTIONALS		
Lighting System (STANDART High Power LED)	🗌 Su	upporting Steel Structure With Post
Lighting System (HDD LUX High Power LED)	🗌 Su	upporting Steel Structure With Post (Hot-dip Galvanized)
Dimmer Kit	□ w	all Installation Steel Beam
Aerofoil Louvre (Line)pc	□ W	all Installation Steel Beam (Hot-dip Galvanized)
Side Raftercm Quantitypc		dditional Post Of Supporting Steel Structurepc
Support Post of Side Raftercm Quantitypc	Ac	dditional Post Of Supp. Steel Str. (Hot-dip Galvanized)pc
Gutter Flush with Rafter (Type B-Flush Finish)		ide Overhang Past Rafter (max. 100cm per side) Type (I/II/III/IV/V/VI) eft Overhang:cm Right Overhang:cm
Additional Railpc	🗌 St	torm Channel for Joining System & Double Rafter Wall racket Kit (for Multiple Systems)
INSTALLATION BRACKET		POST INSTALLATION BASE
🗌 Wall Bracket 🗌 Ceiling Bracket		 Type A (Arch Opening) Type B (Spout)

□ ADDITIONAL NOTES & DRAWINGS ATTACHED